

Bentosteel

Galvanised steel wire mesh for secure installation of Bentorub[®]+



• **field of application** | Secure installation of Bentorub[®]+ in horizontal and vertical applications.

• **advantages** | Easy to install.

• **description** | Galvanised steel wire mesh for secure installation of Bentorub[®]+ in horizontal and vertical applications.

• **application** |

- Install Bentosteel over the Bentorub[®]+ strip.
- Secure Bentorub[®]+ and Bentosteel by nailing (1 nail every 25 cm).

• **technical data/properties**

Property	Value
Wire gauge	0,9 mm
Mesh grid	10,6 by 10,6 mm
Section	25,5 by 9 mm

• **appearance** | Galvanised steel wire mesh.

• **consumption** | 1 metre Bentosteel per linear metre Bentorub[®]+

• **packaging** | Bentosteel: package of 30 x 1 metre.

• **storage** | Unlimited in a dry and cool place.

• **health & safety** | No special recommendations necessary.

All data mentioned on this technical data sheet are product descriptions. They are the result of general experience and experiments and don't take any specific application into account. No further demands may be derived from these data. The manufacturer has the privilege to implement technical changes, which result from new research concerning the material composition and form. To verify that you are holding the latest version of this Technical Data Sheet, please visit www.deneef.eu.

© De Neef Environmental & Chemical group - 19-05-2008-01.